

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/31/2003  
 00000000 EXXON MOBIL

PAGE NO. 1631.1  
 MSDS NO. 1631.1

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

MANUFACTURERS NAME  
 W.M. BARR & COMPANY, INC.

ADDRESS  
 2105 Channel Ave.  
 Memphis, TN 38113 USA

EMERGENCY TELEPHONE #1  
 95-901-775-0100

EMERGENCY CONTACT  
 W.M. Barr Technical Services

EMERGENCY INFORMATION

INVENTORY ITEM #  
 GMS44

CHEMICAL FORMULA  
 1631.1

PRODUCT NAME  
 KLEAN-STRIP MINERAL SPIRITS

REVISED BY  
 W.M. Barr Technical Services

REVISION DATE  
 2/14/1995

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

CARCINOGENICITY

SUBSTANCE DESCRIPTION	PERCENT	CAS#	NTP	ACGIH	OSHA	IARC
-----------------------	---------	------	-----	-------	------	------

SECTION 3. REGULATORY INFORMATION

EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	REG.AGCY	U/M	TWA	STEL	CEIL	SKIN	PEL
-----------------------	----------	-----	-----	------	------	------	-----

ADDITIONAL REGULATORY INFO

CALIFORNIA (PROPOSITION #65)

SEC. 313 SUPPLIER NOTIFICATION

CLEAN AIR ACT

HAZARD COMMUNICATION STANDARD

SECTION 4. HAZARDS IDENTIFICATION

INHALATION ACUTE EXPOSURE EFFECTS

SKIN CONTACT ACUTE EXPOSURE EFFECTS

EYE CONTACT ACUTE EXPOSURE EFFECTS

INGESTION ACUTE EXPOSURE EFFECTS

CHRONIC EXPOSURE EFFECTS

MEDICAL CONDITIONS AGGRAVATED

PRIMARY ROUTE OF EXPOSURE

## MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/31/2003  
00000000 EXXON MOBILPAGE NO. 1631.1  
MSDS NO. 1631.1-----  
SECTION 5. FIRST AID MEASURES  
-----

INHALATION

SKIN CONTACT

EYE CONTACT

INGESTION

NOTE TO PHYSICIAN

-----  
SECTION 6. FIRE FIGHTING MEASURES  
-----

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH	2	1
FLAMMABILITY	2	2
REACTIVITY	0	0
OTHER	G	NA

FLASH METHOD  
TCCFLASH POINT  
107.00 F 41.66 CLOWER EXPLOSION LIMIT  
N/E

GENERAL COMMENTS

EXTINGUISHING METHOD

FIRE FIGHTING PROCEDURES

FIRE AND EXPLOSION HAZARDS

-----  
SECTION 7. ACCIDENTAL RELEASE MEASURES  
-----

CLEAN-UP

WASTE DISPOSAL

-----  
SECTION 8. HANDLING AND STORAGE  
-----

STORAGE

HANDLING

-----  
SECTION 9. TRANSPORT INFORMATION  
-----

TRANSPORTATION

-----  
SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

VENTILATION PROTECTION

## MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/31/2003  
00000000 EXXON MOBILPAGE NO. 1631.1  
MSDS NO. 1631.1-----  
SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION  
(CONTINUED)  
-----

RESPIRATORY PROTECTION

SKIN PROTECTION

EYE PROTECTION

OTHER PROTECTION  
-----SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES  
-----

VOLATILE %

100.000  
por peso

BOILING POINT

GT 316.00 F 157.77 C TEMPS. DE EBULL.: 316°F-360°F

VAPOR DENSITY (Air = 1.0)

Más pesado que el aire

EVAPORATION RATE

Más lento que el éter

BULK DENSITY

6.380  
lbs/gal a 75° F (23.8°C)

pH FACTOR

N/E

PHOTOCHEMICALLY REACTIVE

MAX V.O.C.

MAX VAPOR PRESSURE  
-----SECTION 12. STABILITY AND REACTIVITY  
-----

INCOMPATIBILITIES

DECOMPOSITION

POLYMERIZATION

STABILITY  
-----SECTION 13. ADDITIONAL INFORMATION  
-----

IMPORTANT NOTE