

1. Identification

Product identifier	High Temperature Nickel Anti-Seize Lubricant	
Other means of identification		
FIR No.	195238	
Recommended use	Anti-seize lubricant	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Company Name	Ford Motor Company	
Address	Attention: SDS Information, P.O. Box 1899 Dearborn, Michigan 48121 USA	
Telephone	1-800-392-3673	
SDS Information	1-800-448-2063 (USA and Canada) fordsds.com	
Emergency telephone numbers	Poison Control Center: USA and Canada: 1-800-959-3673 INFOTRAC (Transportation): USA and Canada 1-800-535-5053	

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 4
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Warning	
Hazard statement	May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. May cause long lasting harmful effects to aquatic life.	
Precautionary statement		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.	
Storage	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	May cause irritation of respiratory tract. May be harmful if inhaled. May be irritating to the skin.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
NICKEL		7440-02-0	20 - 25

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician immediately. Rinse mouth. Do not induce vomiting.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Dry sand. Dry chemicals.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire. Carbon dioxide (CO ₂).
Specific hazards arising from the chemical	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Avoid contact with eyes, skin, and clothing. Avoid inhalation of vapors. Ensure adequate ventilation. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. The product is immiscible with water and will sediment in water systems.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes, skin, and clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Provide adequate ventilation. Should be handled in closed systems, if possible. Avoid release to the environment. Observe good industrial hygiene practices. Wear appropriate personal protective equipment. For personal protection, see Section 8 of the SDS.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
NICKEL (CAS 7440-02-0)	PEL	1 mg/m ³

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
NICKEL (CAS 7440-02-0)	TWA	1.5 mg/m ³	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
NICKEL (CAS 7440-02-0)	TWA	0.015 mg/m ³

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust and/or mist, use process enclosure, appropriate local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Suitable chemical protective gloves should be worn when the potential exists for skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Nitrile gloves are recommended.
Other	Wear appropriate chemical resistant clothing if applicable.
Respiratory protection	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Paste.
Color	Grey.
Odor	Hydrocarbon-like.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	449.6 °F (232 °C)
Initial boiling point and boiling range	< 600.8 °F (< 316 °C)

Flash point	429.8 °F (221.0 °C)
Evaporation rate	< 0.01 (BuAc=1)
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	0.9 %
Explosive limit - upper (%)	7 %
Vapor pressure	< 0.01 kPa
Vapor density	> 5 (AIR=1)
Relative density	1.2
Relative density temperature	39.2 °F (4 °C)
Solubility(ies)	
Solubility (water)	NOT SOLUBLE
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 500 °F (> 260 °C)
Decomposition temperature	Not available.
Viscosity	500000 cSt
Viscosity temperature	104 °F (40 °C)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen cyanide (hydrocyanic acid). Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
Skin contact	May be irritating to the skin. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity	May cause respiratory irritation. May irritate eyes and skin.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

NICKEL (CAS 7440-02-0)

2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

NICKEL (CAS 7440-02-0)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged exposure may cause chronic effects. May cause cancer by inhalation.

12. Ecological information

Ecotoxicity May cause long lasting harmful effects to aquatic life.

Ecotoxicity

Components	Species	Calculated/Test Results
NICKEL (CAS 7440-02-0)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.916 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

NICKEL (CAS 7440-02-0)

Listed.

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Serious eye damage or eye irritation
Respiratory or skin sensitization
Carcinogenicity

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
NICKEL	7440-02-0	20 - 25

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

NICKEL (CAS 7440-02-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

California Proposition 65



WARNING: This product can expose you to NICKEL, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

NICKEL (CAS 7440-02-0)

Listed: October 1, 1989

International Inventories

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. Other information, including date of preparation or last revision

Issue date 08-08-2018
Revision date 08-08-2018
Version 03
HMIS® ratings Health: 1
 Flammability: 1
 Physical hazard: 0
NFPA ratings Health: 1
 Flammability: 1
 Instability: 0

Preparation Information and Disclaimer

This document was prepared by FCSD-Toxicology, Ford Motor Company, Fairlane Business Park IV, 17225 Federal Drive, Allen Park, MI 48101, USA, based in part on information provided by the manufacturer. The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user. To the extent that there are any differences between this product's Safety Data Sheet (SDS) and the consumer packaged product labels, the SDS should be followed.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

Part number(s)

XL-2